

### Three-level terminal blocks

... - PV = with equipotential bonding






	gray	PT 1,5/S-3L	3213713	PT 2,5-3L	3210499
	gray	PT 1,5/S-3PV	3213742	PT 2,5-3PV	3210512
	blue	PT 1,5/S-3L BU	3213726	PT 2,5-3L BU	3210509
	green-yellow	PT 1,5/S-3PE	3213739	PT 2,5-3PE	3210525

Width / Length / Height	[mm]	3.5 / 97.2 / 53.2		5.2 / 102 / 58	
Current / voltage // UL	[A] / [V]	15 // 500 / 15 / 600		20 // 500 / 20 / 300	
rigid / AWG // flexible / AWG	[mm <sup>2</sup> ] / [-]	0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14		0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14	
Stranded with ferrule without / with plastic sleeve	[mm <sup>2</sup> ]	0.14 - 1.5 / 0.14 - 1		0.14 - 2.5 / 0.14 - 2.5	
Directly pluggable: with ferrule / rigid	[mm <sup>2</sup> ]	0.34 - 1.5 / 0.25 - 1.5		0.34 - 2.5 / 0.34 - 4	

... PE/L/N = upper level blue, middle level gray, lower level green-yellow with PE foot

... PE/L/L = upper and middle level gray, lower level green-yellow with PE foot



	gray	PT 1,5/S-PE/L/N	3213755	PT 2,5-PE/L/N	3210538	PT 4-PE/L/N	3002614
	gray	PT 1,5/S-PE/L/L	3213768	PT 2,5-PE/L/L	3210541	PT 4-PE/L/L	3002613

Width / Length / Height	[mm]	3.5 / 97.2 / 53.2		5.2 / 102 / 58		6.2 / 119.5 / 56	
Current / voltage // UL	[A] / [V]	15 // 500 / 15 / 600		20 // 500 / 20 / 300		30 // 500 / 20 / 600	
rigid / AWG // flexible / AWG	[mm <sup>2</sup> ] / [-]	0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14		0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14		0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 10	
Stranded with ferrule without / with plastic sleeve	[mm <sup>2</sup> ]	0.14 - 1.5 / 0.14 - 1		0.14 - 2.5 / 0.14 - 2.5		0.25 - 4 / 0.25 - 4	
Directly pluggable: with ferrule / rigid	[mm <sup>2</sup> ]	0.34 - 1.5 / 0.25 - 1.5		0.34 - 2.5 / 0.34 - 4		0.5 - 4 / 0.5 - 6	



	gray	PT 2,5-L/L/N	3210500		
--	------	--------------	---------	--	--

Width / Length / Height	[mm]	5.2 / 102 / 58			
Current / voltage // UL	[A] / [V]	20 // 500 / 20 / 300			
rigid / AWG // flexible / AWG	[mm <sup>2</sup> ] / [-]	0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14			
Stranded with ferrule without / with plastic sleeve	[mm <sup>2</sup> ]	0.14 - 2.5 / 0.14 - 2.5			
Directly pluggable: with ferrule / rigid	[mm <sup>2</sup> ]	0.34 - 2.5 / 0.34 - 4			