


Fuse terminal blocks

Notes:

1) For additional accessories and technical data, see page 98.

2) The current is determined by the fuse used, the voltage by the selected LED display. Observe the maximum power dissipation, see phoenixcontact.net/products.




**6.3 A, lever-type fuse terminal block
for 5 x 20 mm cartridge fuses, 2 function shafts**



Technical data ¹⁾				
Width	Length	Height		
6.2	56	64.8 (NS 35/7,5)		
I_{max} [A]	U_{max} [V]	max. Ø [mm ²]	AWG (UL)	
6.3²⁾	500²⁾	0.2 - 6	24-10	
Maximum bridge current	32 (FBS) / 24 (FBSR)			
Rated data	IEC	UL / CUL	CSA	Ex
Rated voltage	500 ²⁾	300	300	-
Nominal current / cross section	6.3 / 4	6.3 / -	6.3 / -	- / -

Ordering data				
Description	Color	Type	Order No.	Pcs./Pkt.
Fuse terminal block	black	PT 4-HESI (5X20)	① 3211861	50
With LED display 12 ... 30 V AC/DC, 0.31 ... 0.95 mA	black	PT 4-HESILED 24 (5X20)	② 3211903	50
30 ... 60 V AC/DC, 0.40 ... 0.86 mA	black	PT 4-HESILED 60 (5X20)	② 3207908	50
110 ... 250 V AC/DC, 0.41 ... 0.96 mA	black	PT 4-HESILA 250 (5X20)	② 3211907	50

Accessories ¹⁾			
D-ST 4	3030420	50	



**6.3 A, lever-type fuse terminal block
for 5 x 20 mm cartridge fuses**



Technical data ¹⁾				
Width	Length	Height		
8.2	67.8	42.8 (NS 35/7,5)		
I_{max} [A]	U_{max} [V]	max. Ø [mm ²]	AWG (UL)	
6.3²⁾	500²⁾	0.2 - 6	24-10	
Maximum bridge current	-			
Rated data	IEC	UL / CUL	CSA	Ex
Rated voltage	500 ²⁾	300	-	-
Nominal current / cross section	6.3 / 1	6.3 / -	- / -	- / -

Ordering data				
Description	Color	Type	Order No.	Pcs./Pkt.
PTC 4-HESI (5X20)	black	PTC 4-HESI (5X20)	① 3270200	50
PTC 4-HESILED 24 (5X20)	black	PTC 4-HESILED 24 (5X20)	② 3270203	50
PTC 4-HESILED 60 (5X20)	black	PTC 4-HESILED 60 (5X20)	② 3270205	50
PTC 4-HESILA 250 (5X20)	black	PTC 4-HESILA 250 (5X20)	② 3270197	50

Accessories ¹⁾			
D-PTC 2,5-TWIN-MT	3270100	50	


Cover, width: 2.2 mm gray

Terminal blocks – CLIPLINE complete

4 mm² PT Push-in connection terminal blocks

Fuse terminal blocks

Notes:
 1) For additional accessories and technical data, see page 98.
 2) The current is determined by the fuse used.



32 A, fuse terminal block for 5 x 20 mm cartridge fuses



Technical data ¹⁾				
Width	Length	Height		
6.2	118.5	83.9 (NS 35/7,5)		
I _{max.} [A]	U _{max.} [V]	max. Ø [mm ²]	AWG (UL)	
32	500	0.2 - 6	24-10	
32 (FBS) / 24 (FBSR)				
IEC	UL / CUL	CSA	Ex	
500	600	600	-	
28 / 4	6.3 / -	6.3 / -	- / -	
6.3 ²⁾ / 4 (disconnect level)				


Ordering data			
Type	Order No.	Pcs./Pkt.	
PT 4-L/HESI (5X20)	① 3002608	50	
PT 4-L/HESILED 24 (5X20)	② 3002609	50	
PT 4-L/HESILED 60 (5X20)	② 3002611	50	
PT 4-L/HESILED 250 (5X20)	② 3002612	50	

Accessories ¹⁾		
D-PT 4-PE/L/HESI	Order No.	Pcs./Pkt.
D-PT 4-PE/L/HESI	3002619	50

Dimensions	[mm]
Maximum electrical data	
Maximum bridge current	[A]
Rated data	
Rated voltage	[V]
Nominal current / cross section	[A] / [mm ²]
Nominal current / cross section	[A] / [mm ²]

Description	Color
Fuse terminal block with LED for 12 ... 30 V DC, 0.31 ... 0.95 mA	black black
30 ... 60 V AC/DC, 0.40 ... 0.86 mA	black
110 ... 250 V AC/DC, 0.41 ... 0.96 mA	black

Cover, width: 2.2 mm	gray
----------------------	------



32 A, fuse terminal block for 5 x 20 mm cartridge fuses, PE foot




Technical data ¹⁾				
Width	Length	Height		
6.2	118.5	83.9 (NS 35/7,5)		
I _{max.} [A]	U _{max.} [V]	max. Ø [mm ²]	AWG (UL)	
32	500	0.2 - 6	24-10	
32 (FBS) / 24 (FBSR)				
IEC	UL / CUL	CSA	Ex	
500	600	600	-	
28 / 4	6.3 / -	6.3 / -	- / -	
6.3 ²⁾ / 4 (disconnect level)				

Ordering data			
Type	Order No.	Pcs./Pkt.	
PT 4-PE/L/HESI (5X20)	① 3002602	50	
PT 4-PE/L/HESILED 24 (5X20)	② 3002603	50	
PT 4-PE/L/HESILED 60 (5X20)	② 3002604	50	
PT 4-PE/L/HESILED 250 (5X20)	② 3002605	50	

Accessories ¹⁾		
D-PT 4-PE/L/HESI	Order No.	Pcs./Pkt.
D-PT 4-PE/L/HESI	3002619	50

Fuse terminal blocks

Notes:
 1) For additional accessories and technical data, see page 98.
 2) The current is determined by the fuse used, the voltage by the LED display.
 3) 15 A for single arrangement, 10 A for group arrangement. For the derating curve, see phoenixcontact.net/products. The recommended continuous load capacity of fuse inserts in accordance with DIN 72581/Part 3 is a maximum of 80% of their nominal current (at an ambient temperature of 23°C).



15 A, fuse terminal block, for type F flat-type fuses




Technical data ¹⁾				
Width	Length	Height		
6.2	56	36.5 (NS 35/7,5)		
I _{max.} [A]	U _{max.} [V]	max. Ø [mm ²]	AWG (UL)	
15 ³⁾	400 ²⁾	0.2 - 6	24-10	
32 (FBS) / 24 (FBSR)				
IEC	UL / CUL	CSA	Ex	
400 ²⁾	300	300	-	
10 ²⁾ / 4	7.5 / -	15 / -	- / -	

Ordering data			
Type	Order No.	Pcs./Pkt.	
PT 4-FSI/F	① 3208943	50	

Accessories ¹⁾		
D-ST 4	Order No.	Pcs./Pkt.
D-ST 4	3030420	50

Description	Color
Fuse terminal block with LED display for 12 V DC, 1.7 mA	black black
for 24 V DC, 1.9 mA	black

Cover, width: 2.2 mm	gray
----------------------	------



15 A, fuse terminal block with LED display, for type F flat-type fuses



Technical data ¹⁾				
Width	Length	Height		
6.2	56	36.5 (NS 35/7,5)		
I _{max.} [A]	U _{max.} [V]	max. Ø [mm ²]	AWG (UL)	
15 ³⁾	12 ²⁾	0.2 - 6	24-10	
32 (FBS) / 24 (FBSR)				
IEC	UL / CUL	CSA	Ex	
12 ²⁾	300	12	-	
10 ²⁾ / 4	7.5 / -	15 / -	- / -	

Ordering data			
Type	Order No.	Pcs./Pkt.	
PT 4-FSI/F-LED 12	① 3208951	50	
PT 4-FSI/F-LED 24	① 3208964	50	

Accessories ¹⁾		
D-ST 4	Order No.	Pcs./Pkt.
D-ST 4	3030420	50